



**DIPLOMATIC
HYDRAULICS**

P2A*L

MANIFOLDS FOR CETOP 03 VALVES WITH SIDE PORTS SERIES 11

- The P2A*L series of manifolds is designed for connection in parallel of two or more CETOP 03 valves.
- The monocast design enables the simple creation of circuits without the use of pipes and fittings, thereby reducing overall dimensions to a minimum.
- All sections feature a common pressure and discharge fitting on both ends of the subplate.
- Maximum flow rate can be increased up to double the output if the sub-plates are powered at both ends.
- Each section is fitted with work ports A and B positioned on the side of the sub-plate.
- Subplates are available in aluminium.

p max 210 bar

Q max 50 l/min

Performance ratings			
Maximum operating pressure	- P-A-B ports	bar	210
	- T port	bar	140
Maximum flow		l/min	50
Ports dimensions:	P - port (pressure)	BSP	1/2"
	T - port (drainage)	BSP	1/2"
	A - port	BSP	3/8"
	B - port	BSP	3/8"
Ambient temperature range		°C	-20 ÷ +50
Fluid temperature range		°C	-20 ÷ +80
Fluid viscosity range		cSt	10 ÷ 400
Recommended viscosity		cSt	25
Fluid contamination range	According to NAS 1638 class 10		

1 - IDENTIFICATION CODE



